




# LXS

Polycarbonate Side-Folding Accordion Door





# LXS

## Polycarbonate Side-Folding Accordion Door



**A**lumatec Pacific Products side folding accordion is a beautiful combination of security and style. Our LXS is manufactured using clear 3/32" polycarbonate windows which provide years of security, aid in temperature control and store cleanliness, and prevent reach through theft. Additionally, this style of door is designed to allow maximum storefront merchandising and product visibility, while providing strength and durability that will outlast any other side folding door.




### Standard Features:

- 99.9% enclosed curtain.
- Accommodates openings up to 16' tall.
- Each piece of polycarbonate is framed to prevent abrasions of the windows, thus maintaining clear visibility of the merchandise even after years of use.
- Radius Options of: 30° (14"), 45° (14"), 90° (14") or a custom continuous curve.




# Design Specifications


## Post Section View:




## Post Plan View:





## Track Profiles



## Model: LXS (single slide with intermediate post)



## Stacking see detail [A1]



## Available Finishes

	Clear	White	Light Gray	Bronze	Black
Polycarbonate	✓	✓	✓		✓
Aluminum	✓			✓	✓

\*\*See our website for complete choice of Powder Coat color options\*\*

# Alumatec Pacific Products Model: LXS (Polycarbonate Side-Folding Accordion Door)

## **PART 1 GENERAL**

### **1.1 SUMMARY**

A. Aluminum side-folding accordion door manufactured by **Alumatec Pacific Products** is as shown on this submittal.  
B. Design, construction and preparation of openings, including support header (see standard manufacturer drawing details), backing at leading edge wall to connect locking wall strike, and pocket by others. Finish or field painting is excluded (unless included in proposal or specification, job specific).

### **1.2 SYSTEM DESCRIPTION**

A. Side-Folding doors are designed for standard cycle usage, and designed for manual push / pull operation.

### **1.3 WARRANTY**

A. Limited (see warranty sheet) two years from date of shipment – warranty does not apply to finishes.

## **PART 2 PRODUCTS**

### **2.01 MANUFACTURER**

A. **Alumatec Pacific Products:** 1155 West 500 North, Centerville, UT 84014 – [www.alumatecpp.com](http://www.alumatecpp.com)

B. **Sales Department:** 801-298-0181 ext. 1 or toll free 877-770-0181 ext. 1

### **2.02 MATERIALS**

A. **Curtain** is assembled from custom designed, extruded, full height interlocking hinge system, using pure US billet aluminum. Standard finish to be commercial clear satin anodized. Panels constructed with clear view polycarbonate at 3/32" thick x 48" or less in height; each with a 4" top and bottom kick plate and 4" tall intermediate stile. Extruded interlocking hinge system every 7" on horizontal centers. Each panel is fabricated to opening size less 1½" gap at top of curtain (between curtain and track), and 1½" gap between floor and bottom of curtain slat.

B. **Locking Mullion:** is a rectangular shape extruded from 6063-alloy aluminum, and constructed with a locking system to prevent access by pulling out or pushing in on the curtain.

☐ [#1] Hook Lock – Standard locking mullion at leading edge of side-folding door (full height wall strike included).

☐ [#2] Intermediate Drop Lock – Installed every 10 feet in width with keyed cylinder exterior (keyed cylinder or thumb turn cylinder can be added to interior if specified). Drop pin constructed of 7/16" cold drawn round with 3" throw capacity into stainless steel dust proof floor strike.

☐ [#3] Bi-Parting Lock – Locking mullions to consist of #1 hook lock and #2 drop lock with strike on intermediate post. Hook lock to engage into strike, while #2 drop lock to be locked into floor. This allows the door to be opened in a specific spot (in front of man door) or standard, in the center of the opening. Door to stack at each jamb.

☐ [#4] Top & Bottom Lock – Used when lead post terminates at glass, or any object that is not a flat surface where the wall strike cannot be mounted. Top pin and drop pin constructed of 7/16" cold drawn round with 3" throw capacity into stainless steel dust proof floor strike.

☐ [#5] Free Floating Tailing Edge – Floating tailing edge for pocket application. Free floating mullion to be set to float in pocket but not allow door to travel past front edge of pocket. V-Stop fabricated from ¾" steel angle set with anchors provided at pocket depth taking up all slack in curtain (curtain to be snug when in the locked position).

☐ [ST] Stationary Wall Mullion – To be permanently attached to wall when storage pocket is not used.

### **C. Top Track**

☐ V3 (replacement for V1) 1½" wide by 1½" tall – standard (black roller / wheel bearings).

☐ V2 (used for all large openings or under drop ceiling applications) 1¼" x 1¼" (white roller / wheel bearings).

### **D. Radius Track**

☐ 14" 90°R ☐ 14" 45°R ☐ 14" 30°R ☐ Custom continuous sweeping radius (consult radius dimension / help finder drawing detail).

### **E. Operation**

Manual push / pull

### **F. Locking (is as indicated):**

a. ☐ CYLINDER LOCK standard interior & exterior on lead post. Keyed cylinder standard on one side (interior or exterior) on #2 Intermediate mullions, as indicated and shown on the submittal drawing.

i. ☐ Keyed Cylinder Exterior ☐ Thumb-Turn Cylinder Interior or ☐ Keyed Cylinder Interior

☐ Standard Schlage Keyway Cylinder

☐ Best Interchangeable Core Cylinder (Medeco, KeyMark, Falcon, etc.)

### **2.03 FINISHES**

A. Aluminum curtain finish as indicated:

☐ Clear Anodized (standard) ☐ Black Anodized ☐ Bronze Anodized

## **PART 3 EXECUTIONS**

### **3.01 INSTALLATION**

A. Doors are to be installed in accordance with Alumatec Pacific Products installation instructions and by authorized, and certified professional Alumatec Pacific Products door dealer.



1155 West 500 North  
Centerville, Utah 84014  
Tel: 801.298.0181 Fax: 801.298.0905  
Toll Free: 877.770.0181 ext 1

see us at  
**Sweets**.com

[www.alumatecpp.com](http://www.alumatecpp.com) • [info@alumatecpp.com](mailto:info@alumatecpp.com) • [sales@alumatecpp.com](mailto:sales@alumatecpp.com)